

钻头 Drill bit	钎头直径 Diameter		合金数量×直径 Noxbutton diameter			水孔数量 Flushing hole		重量 Weight approx kg	型号 P/N
	毫米 mm	英寸 inch	芯齿 Front	边齿 Gauge	倾角 Angle	正 Front	侧 Side		
柱齿形钎头 Button bit 	圆齿 Spherical buttons								
	92	35/8	4x13,1x13	8x13	35°	4	-	5.3	1432-92T60-513/813-45-31
	96	33/4	4x13,1x13	8x14	35°	4	-	5.6	1432-96T60-513/814-45-31
	102	4	9x11	9x13	35°	3	-	6.0	1431-102T60-911/913-45-31
	115	41/2	10x12	9x14	35°	3	-	6.8	1431-115T60-1012/914-45-31
	127	5	10x13	9x14	35°	3	-	7.5	1431-127T60-1013/914-45-31
	140	51/2	10x14	9x16	35°	3	-	9.0	1431-140T60-1014/916-45-31
	152	6	12x14	9x16	35°	3	-	10.6	1431-152T60-1214/916-45-31
	抛物线齿 Parabolic buttons								
	92	35/8	4x13,1x13	8x13	35°	4	-	5.3	1432-92T60-513/813-45-51
	96	33/4	4x13,1x13	8x14	35°	4	-	5.6	1432-96T60-513/814-45-51
	102	4	9x11	9x13	35°	3	-	6.0	1431-102T60-911/913-45-51
	115	41/2	10x12	9x14	35°	3	-	6.8	1431-115T60-1012/914-45-51
	127	5	10x13	9x14	35°	3	-	7.5	1431-127T60-1013/914-45-51
140	51/2	10x14	9x16	35°	3	-	9.0	1431-140T60-1014/916-45-51	
152	6	12x14	9x16	35°	3	-	10.6	1431-152T60-1214/916-45-51	
柱齿易返钎头 Retrac button bit 	圆齿 Spherical buttons								
	92	35/8	9x12	9x12	40°	2	-	5.4	1531-92T60-912/912-45-31
	96	33/4	9x12	9x12	40°	2	-	6.3	1531-96T60-912/912-45-31
	102	4	10x12	9x13	40°	2	-	7.3	1531-102T60-1012/913-45-31
	115	41/2	10x12	9x14	35°	3	-	9.8	1531-115T60-1012/914-45-31
	118	45/8	6x13	9x16	35°	3	-	10.0	1531-118T60-613/916-45-31
	127	5	10x13	9x14	35°	3	-	12.0	1531-127T60-1013/914-45-31
	140	51/2	10x14	9x16	35°	3	-	14.0	1531-140T60-1014/916-45-31
	152	6	12x14	9x16	35°	3	-	16.0	1531-152T60-1214/916-45-31
	抛物线齿 Parabolic buttons								
	92	35/8	9x12	9x12	40°	2	-	5.4	1531-92T60-912/912-45-51
	96	33/4	9x12	9x12	40°	2	-	6.3	1531-96T60-912/912-45-51
	102	4	10x12	9x13	40°	2	-	7.3	1531-102T60-1012/913-45-51
	115	41/2	10x12	9x14	40°	3	-	9.8	1531-115T60-1012/914-45-51
118	45/8	6x13	9x16	35°	3	-	10.0	1531-118T60-613/916-45-51	
127	5	10x13	9x14	35°	3	-	12.0	1531-127T60-1013/914-45-51	
140	51/2	10x14	9x16	35°	3	-	14.0	1531-140T60-1014/916-45-51	
152	6	12x14	9x16	35°	3	-	16.0	1531-152T60-1214/916-45-51	

深孔螺纹钎具 Bench drilling

T60

钎杆 Drill rod	长度 Length		外径 Diameter		重量 Weight approx kg	型号 P/N	
	毫米 mm	英尺 Foot	毫米 mm	英寸 Inch			
快接钎杆 适用于96mm钎头 MF-rod, For bits from 96mm 内孔 Flushing hole 22.5mm.	3660	12'	60	2 3/8	73.9	24R60-T60/85-3660-23	
	4265	14'	60	2 3/8	85.5	24R60-T60/85-4265-23	
	6095	20'	60	2 3/8	116.6	24R60-T60/85-6095-23	
	4265	14'	64	2 1/2	95.0	24R64-T60/85-4265-23	
	快接钎杆 适用于92-115mm钎头 MF-rod, For bits from 92-115mm 内孔 Flushing hole 22.6mm.	3660	12'	60	2 3/8	73.9	24R60-T60/82-3660-23
		4265	14'	60	2 3/8	85.5	24R60-T60/82-4265-23
		6095	20'	60	2 3/8	116.6	24R60-T60/82-6095-23
	导向钎杆 快接头直径85mm (76mm钎杆直径是82mm) Pilot Tube Female end OD 85mm (82mm on 76mm tubes)	1600	5'3"	87	3 1/2	39.0	24G87-T60/85-1600-23
		4265	14'	87	3 1/2	99.0	24G87-T60/85-4265-23
		5335	17'6"	76	3	124.9	24G76-T60/85-5335-23
	钻杆 Drill Tube	3660	12'	87	3 1/2	87.8	24G87-T60/87-3660-23
		4265	14'	87	3 1/2	99.0	24G87-T60/87-4265-23

SHANDONG TAISHAN ROCK TOOLS CO., LTD

Mr:Rock Sui

Tel: 0086-635-6515509

Fax:0086-635-6515678

Mobile: +86 135 6302 6509

+86 138 6352 6509

Email:chinarocktool@163.com

rockdrillingtools@163.com

export@china-rocktool.com

export@rockdrillingtools.com

WeChat: +86 13563026509

WhatsApp: +86 135 6302 6509

SKYPE: sui671100

Website: www.rockdrillingtools.com

www.china-rocktool.com

**ADD: Xihu Town 10 #, Yanggu ,Liaocheng city , Shandong
province , China**